



LGR 7000XLi Dehumidifier

Portable, high-performance water removal – even at low humidity levels. Reduce and control excess moisture fast with the unit's patented cross-flow technology that optimizes moisture removal in virtually all conditions. The i-Series digital control displays real-time temperature, relative humidity and GPP, and offers an adjustable humidistat for precise moisture control.



FEATURES

- Advanced Crossflow Technology maximizes efficiency and ensures superior performance in low-grain conditions
- Built-in sensors monitor performance parameters; system automatically adjusts operation to optimize performance in all conditions
- Built-in humidistat and plain-English system status and maintenance-related messages
- Sealed large-capacity pump basin large enough to contain water from an unintentional defrost after a power outage or other unexpected shut-down
- Ergonomic design. Handle 2 in. taller for easier use on stairs, folds down for storage. Integrated cord and hose storage.

SPECIFICATIONS

- Water removal AHAM (80°F/60%RH): 130 pts. | 61.5 L / day
- Max. water removal (saturation): 235 pts. | 111 L / day
- Process air (max.): 325 CFM | 552 CMH. Floor-level outlet.
- **Dimensions (W × H × D)**: 33.5 × 20 × 20 in. | 85 × 51 × 51 cm
- Use weight: 107 lbs. | 49 kg

SIZES • OPTIONS

F412

