

Dehumidifiers

LGR 6000Li

Get the quietest and best-performing compact, easy-transport i-Series dehumidifier your techs will always choose first. The LGR 6000Li is perfectly sized for everyday jobs, and it's Dri-Eaz rugged, ready to withstand years of heavy use. Removes more water than any other competitive unit in its class. Displays grain depression, graphs drying progress, provides quick access to humidistat settings, and more. Features the new [Command Hub](#), compatible with the new Command Center App. Take advantage of Bluetooth and WiFi connectivity to control the dehu and view jobsite conditions remotely. Available in early 2023 in the [Apple Store](#) and [Google Play Store](#).

Features

- NEW! Command Hub touchscreen controller displays real-time temp, RH, grain depression and drying progress trends at a glance. Controller integration product for existing i-Series dehumidifiers also available. [Learn more](#).
- Extreme Dewpoint Technology™ (EDT) delivers the fastest response to changing conditions.
- Fast and convenient access to humidistat, job hours, maintenance reminders and more.
- Process outlet fits 12 in. layflat and rigid ducting.
- Uses all-in-one 4-PRO filter: electrostatic mesh filtration with antimicrobial treatment and odor-fighting carbon.
- Easily ductable using built-in snap-ring mount on air outlet.
- Unique spill-proof pump basin keeps in any water left after the final purge cycle.
- Fast 4-bolt access for easy cleaning and preventive maintenance.
- Practically indestructible, rolls up stairs easily and stacks for storage.

Specifications

- **Water removal AHAM (80°F/60% RH):** 100 pts. | 47.3 liters / day
- **Water removal Saturation (90°F/90% RH):** 204 pts. | 96.5 liters / day
- **Water removal LGR (80°F/20% RH):** 40% higher than competitive units
- **Process air (max.):** 320 CFM
- **Dimensions (H × D × W):** 32.1 × 19.8 × 20.0 in. | 81.5 × 50.3 × 50.8 cm
- **Weight:** 103 lbs. | 46.7 kg
- **Amps:** 6.6A
- **Volts:** 115V
- **Frequency:** 60Hz
- **Power:** 759W
- **Operating range:** 33°F–100°F | 1°C–38°C
- **Noise level (avg.):** 53 dB
- **Drain hose:** 40 ft. | 12.2 m
- **Power cord:** 25 ft. | 7.6 m
- **Housing:** Rotomolded polyethylene
- **Air filter:** 4-PRO filter
- **Safety:** ETL listed CSA 22.2 no. 92
- **Xactimate:** WTRDHM>L

Sizes ▪ Options

- 103614 (F600): One unit